



Scanna för pris
& tillgänglighet

SALT

EN 14411 Ala UGL (Unglazed)



VÄGG- OCH GOLVPLATTOR Matt

FORMAT VÄGG- OCH GOLVPLATTOR

597x597x9 mm Rett



FÄRGER



Beige
1046-0002



Grey
1046-0003



Ocre
1046-0004

297x297x8 mm R10 B

FORMBITAR



297X297X8 Stair tread

1046-0011 Beige
1046-0012 Grey
1046-0013 Ocre



297X297X8 Stair tread nose

1046-0014 Beige
1046-0015 Grey
1046-0016 Ocre



80X297X8 Skirting

1046-0008 Beige
1046-0009 Grey
1046-0010 Ocre



150X297X8 Grid

1046-0005 Beige
1046-0006 Grey
1046-0007 Ocre



30X297X8 External Profile

1046-0017 Beige
1046-0018 Grey
1046-0019 Ocre



30X297X8 Internal Profile

1046-0017 Beige
1046-0018 Grey
1046-0019 Ocre

TEKNISKA DATA

EN 14411 Ala

FEATURES	Unit of mesurement	Mean value	Fixed value	Test method
Dimensions-Length and width	%	Conform	+/- 2,0 MAX +/-4,0 mm	UNI EN ISO 10545-2
Side straightness	%	Conform	+/- 1,5 MAX	UNI EN ISO 10545-2
Corner squareness	%	Conform	+/- 1,5 MAX	UNI EN ISO 10545-2
Flatness	%	Conform	+/- 1,5 MAX	UNI EN ISO 10545-2
Thickness	%	Conform	+/- 5 MAX	UNI EN ISO 10545-2
Surface quality	%	Conform	≤95%	UNI EN ISO 10545-2
Water absorption	%	Conform	≤ 0,5	UNI EN ISO 10545-3
Breaking strenght	N	Conform	≥ 1300 se sp ≥7,5 mm ≥ 600 se sp <7,5 mm	UNI EN ISO 10545-4
Modulus of rupture	N/mm2	Conform	≥ 28 N/mm2	UNI EN ISO 10545-4
Frost resistance	-	Conform	Pass	UNI EN ISO 10545-12
Resistance to chemicals for household use	-	Conform	B MIN	UNI EN ISO 10545-13