



Scanna för pris
& tillgänglighet

KLINK


EN 14411 B1a UGL (Unglazed)



VÄGG- OCH GOLVPLATTOR Matt

FORMAT VÄGG- OCH GOLVPLATTOR


297x297x8 mm R10 B




FÄRGER



Flaming Grey
1060-0001



Flaming Ocre
1060-0002



Flaming Red
1060-0003

297x297x8 mm R10 B

FORMBITAR- STAIRTILE & SKIRTINGS



297X297X8 Stair tread



297X297X8 Stair tread nose



80X297X8 Skirting



1060-0010 Flaming Grey
1060-0011 Flaming Ocre
1060-0012 Flaming Red



1060-0013 Flaming Grey
1060-0014 Flaming Ocre
1060-0015 Flaming Red



1060-0007 Flaming Grey
1060-0008 Flaming Ocre
1060-0009 Flaming Red



150X297X8 Grid



30X297X8 External Profile



30X297X8 Internal Profile



1060-0004 Flaming Grey
1060-0005 Flaming Ocre
1060-0006 Flaming Red



1060-0016 Flaming Grey
1060-0017 Flaming Ocre
1060-0018 Flaming Red



1060-0019 Flaming Grey
1060-0020 Flaming Ocre
1060-0021 Flaming Red

TEKNISKA DATA

EN 14411 Ala

FEATURES	Unit of mesurement	Mean value	Fixed value	Test method
Dimensions-Length and width	%	Conform	+/- 2,0 MAX +/-4,0 mm	UNI EN ISO 10545-2
Side straightness	%	Conform	+/- 1,5 MAX	UNI EN ISO 10545-2
Corner squareness	%	Conform	+/- 1,5 MAX	UNI EN ISO 10545-2
Flatness	%	Conform	+/- 1,5 MAX	UNI EN ISO 10545-2
Thickness	%	Conform	+/- 5 MAX	UNI EN ISO 10545-2
Surface quality	%	Conform	≤95%	UNI EN ISO 10545-2
Water absorption	%	Conform	≤ 0,5	UNI EN ISO 10545-3
Breaking strenght	N	Conform	≥ 1300 se sp ≥7,5 mm ≥ 600 se sp <7,5 mm	UNI EN ISO 10545-4
Modulus of rupture	N/mm2	Conform	≥ 28 N/mm2	UNI EN ISO 10545-4
Frost resistance	-	Conform	Pass	UNI EN ISO 10545-12
Resistance to chemicals for household use	-	Conform	B MIN	UNI EN ISO 10545-13